





Construction Products Regulation

Declaration of Performance

Identification Code: ER1
Certificate Number: HS/FA/CH/CO/ER1

Serial number: None

Intended use: Concrete lintel intended for use in walls and partitions

Manufacturer: Naylor Concrete Products Ltd, Whaley Road, Barugh Green, Barnsley, South Yorkshire, S75 1HT

Assessment and verification of constancy of performance: System 3

Relevant harmonised standard: EN 845-2:2016

Lucideon Ltd (Notified Body No.1289) carried out initial type testing to EN845-2:2016 under AVCP system 3 and issued test report Ref: UK20866/Ref.1/CR2

Declared Performance

| ER1 | Lintel Length | | | | | | | | | | | |
|---|--|------|------|------|------|------|------|--|--|--|--|--|
| Essential Characteristics | 900 | 1100 | 1200 | 1500 | 1800 | 2100 | 2400 | | | | | |
| Load bearing capacity (kNm-1) | 8.31 | 5.07 | 4.88 | 2.32 | 1.78 | 1.19 | 0.84 | | | | | |
| Deflection at 1/3 of load capacity (mm) | 2.81 | | | | | | | | | | | |
| Thermal resistance | Thermal conductivity λ 10,dry, mat (according to EN 1745) 1.52 W/m.K | | | | | | | | | | | |
| Resistance to fire | 30 minutes | | | | | | | | | | | |
| Durability of performance characteristics against corrosion | C2 - from table C3 EN 845-2:2016 (E) | | | | | | | | | | | |
| Durability of performance characteristics against freeze/thaw cycle | Resistant | | | | | | | | | | | |
| Water absorption | 1.15 C _{w.s} | | | | | | | | | | | |
| Water vapour permeability | NPD | | | | | | | | | | | |
| Dangerous substances | None | | | | | | | | | | | |

Signed for and on behalf of the manufacturer by: