



**Construction Products Regulation  
Declaration of Performance**

**Identification Code: ER6E**  
**Certificate Number: HS/FA/CH/CO/ER6E**

*Serial number:* None

*Intended use:* Concrete lintel intended for use in walls and partitions

*Manufacturer:* Naylor Concrete Products Ltd, Whaley Road, Barugh Green, Barnsley, South Yorkshire, S75 1HT

*Assessment and verification of constancy of performance:* System 3

*Relevant harmonised standard:* EN 845-2:2013

*Lucideon Ltd (Notified Body No.1289) carried out initial type testing to EN845-2:2013 under AVCP system 3 and issued test report Ref: 132024/Ref 7*

**Declared Performance**

ER6 – ON EDGE	Lintel Length											
Essential Characteristics	900	1100	1200	1350	1500	1800	2100	2400	2700	3000		
Load bearing capacity (kNm <sup>-1</sup> )	36.87	23.06	18.87	14.41	13.25	8.51	5.86	4.23	3.15	2.41		
Deflection at 1/3 of load capacity (mm)	1.16											
Thermal resistance	Thermal conductivity $\lambda_{10,dry,mat}$ (according to EN 1745) 1.52 W/m.K											
Resistance to fire	30 minutes											
Durability of performance characteristics against corrosion	C2 - from table C3 EN 845-2:2013 (E)											
Durability of performance characteristics against freeze/thaw cycle	Resistant											
Water absorption	1.15 C <sub>w,s</sub>											
Water vapour permeability	NPD											
Dangerous substances	None											

*The performance of the product identified is in conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer identified.*

Signed for and on behalf of the manufacturer by:

**H MacIntosh**, (Divisional Director), Barugh Green, 17<sup>th</sup> March 2017