

NAYLOR
CONCRETE

Made in the UK
Excellent Construction Products



145



215

Construction Products Regulation
Declaration of Performance

Identification Code: R7
Certificate Number: HS/FA/CH/CO/R7

Serial number: None

Intended use: Concrete lintel intended for use in walls and partitions

Manufacturer: Naylor Concrete Products Ltd, Whaley Road, Barugh Green, Barnsley, South Yorkshire, S75 1HT

Assessment and verification of constancy of performance: System 3

Relevant harmonised standard: EN 845-2:2013

Lucideon Ltd (Notified Body No.1289) carried out initial type testing to EN845-2:2013 under AVCP system 3 and issued test report Ref: 16904/Ref.1/CR1

Declared Performance – Standard / Fair Faced

HI SPEC R7 – 120 MINS FIRE	Lintel Length											
	900	1100	1200	1500	1800	2100	2400	2700	3000	3300	3600	
Essential Characteristics												
Load bearing capacity (kNm ⁻¹)	24.88	18.64	16.62	13.13	10.54	8.59	7.22	5.44	4.17	3.26	2.78	
Deflection at 1/3 of load capacity (mm)	2.94											
Thermal resistance	Thermal conductivity $\lambda_{10, dry, mat}$ (according to EN 1745) 1.52 W/m.K											
Resistance to fire	120 minutes											
Durability of performance characteristics against corrosion	C2 - from table C3 EN 845-2:2013 (E)											
Durability of performance characteristics against freeze/thaw cycle	Resistant											
Water absorption	1.15 C _{w,s}											
Water vapour permeability	NPD											
Dangerous substances	None											

The performance of the product identified is in conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer identified.

Signed for and on behalf of the manufacturer by:

H MacIntosh, (Divisional Director), Barugh Green, 17th March 2017