

NAYLOR
CONCRETE

Made in the UK
Excellent Construction Products



215



100

Construction Products Regulation
Declaration of
Performance

Identification Code: R9
Certificate Number: HS/FA/CH/CO/R9

Serial number: None

Intended use: Concrete lintel intended for use in walls and partitions

Manufacturer: Naylor Concrete Products Ltd, Whaley Road, Barugh Green, Barnsley, South Yorkshire, S75 1HT

Assessment and verification of constancy of performance: System 3

Relevant harmonised standard: EN 845-2:2016

Lucideon Ltd (Notified Body No.1289) carried out initial type testing to EN845-2:2016 under AVCP system 3 and issued test report Ref: UK20866/Ref.1/CR2

Declared Performance – Standard / Fair Faced

HI SPEC R9	Lintel Length											
Essential Characteristics	900	1100	1200	1500	1800	2100	2400	2700	3000	3300	3600	
Load bearing capacity (kNm ⁻¹)	78.18	62.44	55.80	38.70	27.90	21.20	16.80	13.60	11.30	9.53	8.20	
Deflection at 1/3 of load capacity (mm)	3.82											
Thermal resistance	Thermal conductivity $\lambda_{10,dry,mat}$ (according to EN 1745) 1.52 W/m.K											
Resistance to fire	30 minutes											
Durability of performance characteristics against corrosion	C2 - from table C3 EN 845-2:2016 (E)											
Durability of performance characteristics against freeze/thaw cycle	Resistant											
Water absorption	1.15 C _{w,s}											
Water vapour permeability	NPD											
Dangerous substances	None											

Signed for and on behalf of the manufacturer by:

H MacIntosh, (Divisional Director), Barugh Green, 18th November 2020